



VITEX THERM

Σύστημα Εξωτερικής Θερμομόνωσης
Thermal Insulation System

GRANIKOT PRIMER

Acrylic Textured Primer

Acrylic textured primer ideal for interior and exterior surfaces of plaster, concrete and surfaces coated with water-based paints (emulsions, acrylics, etc.). Improves the appearance, hiding power, adhesion and durability of acrylic and silicone plasters GRANIKOT on smooth or uneven surfaces. It is part of the External Thermal Insulation Composite System (ETICS) VITEX THERM, which is certified with the CE marking according to the requirements of EAD 040083-00-0404.



Advantages:

- Ideal for interior and exterior smooth or rough surfaces
- Improves the hiding power and adhesion of Granikot plasters

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

1300-1800 cps (BROOKFIELD
sp.3/20rpm, 25°C)

Density

1,27 ± 0,02 Kg / L (ISO 2811)

APPLICATION

For exterior and interior surfaces
(plaster, concrete, facade thermal
insulation systems- ETICS)

COLOURS

White



COVERAGE



One coat

10-12 m²/L

DILUTION



Water

0-3%

DRYING TIME



Touch dry

45 min

For plaster application

2-4 h

PACKAGING

White	3 L	10 L
Base	3 L	10 L





VITEX THERM

Σύστημα Εξωτερικής Θερμομόνωσης
Thermal Insulation System

APPLICATION

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.

STEPS OF APPLICATION

1

Dilute 0-3% with water and stir well before use.

2

Apply one coat by brush or roller.

TOP COAT APPLICATION



Apply after 2-4 hours any Granikot finishing plaster.



TIPS

- Application at 5-35°C and <80% RH. For exterior use, do not apply if there is a risk of rain/frost in the next 48 hours and strong wind conditions.
- Protect surfaces from direct sunlight to prevent uneven drying.
- Tools must be cleaned immediately

- after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Primers": VOC content limit **30 g/L**.
Maximum VOC content **29 g/L** VOCs
(ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.
Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Containers must be kept closed in a shady place away from direct sunlight, maximum 24 months from date of production.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

