



# VITEX THERM

Σύστημα Εξωτερικής Θερμομόνωσης  
Thermal Insulation System

## VT-20

### Acrylic dispersion for mortar improvement

Synthetic emulsion admixture for mortars, ideal for enhancing the sealing mortar VT-10, where the requirements for sealing and flexibility are very high (e.g. external insulation system). It improves workability while increasing the mechanical and chemical strength. It is useful in any building work, plastering and filling of floors (cement screeds).

#### Advantages:

- Admixture emulsion for enhancing VT-10



## PRODUCT FEATURES

### PACKAGING

Available in 5 Kg cans



### VOCS (Volatile Organic Compounds)



EU maximum VOC content limit values (Directive 2004/42/CE) for this product (category **A/h** "Binding primers", Type **WB**): **30 g/L**. The product contains maximum **3 g/L** VOCs (ready to use product).

## APPLICATION

### APPLICATION FIELD



Add the content of VT-10 of 25 Kg to 5 Kg of the acrylic dispersion VT-20 under constant stirring, to get a homogeneous paste suitable for coating.

### TIPS

- In other applications diluted in mortar's water before mixing in a ratio (VT-20: water) 1:1 to 1:3 depending on application and technical requirements.
- Stir well before use.
- Do not apply at temperatures below 5°C higher than 35°C.
- The above application guidelines are indicative, for the correct use of the product.
- For more technical details please contact the company's technical department.

## ADDITIONAL INFORMATION

### STORAGE



Containers must be kept closed in a cool, dry, well ventilated area protected from direct sunlight at temperatures between 5°C - 38°C.

### SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet. Poisons Control Centre Tel.: +30 210 7793 777

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.



VITEX S.A., P.O. Box. 139 Imeros Topos, Aspropyrgos GR 193 00 | Tel. +30 210 5589500, Fax +30 210 4835007 | www.vitextherm.gr

**+30.210.5589.400**  
TECHNICAL SUPPORT



Version: 11.2021 (This datasheet supersedes all previous versions)